



Product Service

Attestation of Conformity

No. N8A 084752 0028 Rev. 01

Holder of Certificate: **München Energieprodukte GmbH**
Stethaimerstr. 32-34
84034 Landshut
GERMANY

Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
Mono-Crystalline Silicon Photovoltaic Module

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 704062032201-01

Date, 2021-04-01

(Zhulin Zhang)

Page 1 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 084752 0028 Rev. 01

Model(s):

MSMDxxxM2-36, xxx =320 to 375 in steps of 5
 MSMDxxxM2-30, xxx =270 to 315 in steps of 5
 MSMDxxxM2-27, xxx =240 to 265 in steps of 5
 MSMDxxxM2-18, xxx =160 to 185 in steps of 5
 MSMDxxxM3-36, xxx =350 to 400 in steps of 5
 MSMDxxxM3-30, xxx =290 to 330 in steps of 5
 MSMDxxxM3-27, xxx =270 to 300 in steps of 5
 MSMDxxxM3-24, xxx =230 to 265 in steps of 5
 MSMDxxxM3-18, xxx =175 to 200 in steps of 5
 MSMDxxxM2-72, xxx =345 to 410 in steps of 5
 MSMDxxxM2-60, xxx =300 to 340 in steps of 5
 MSMDxxxM3-72, xxx =380 to 420 in steps of 5
 MSMDxxxM3-60, xxx =320 to 350 in steps of 5
 MSMDxxxM6-72, xxx =430 to 460 in steps of 5
 MSMDxxxM6-60, xxx =355 to 380 in steps of 5
 MSMDxxxM10-72, xxx=525 to 545 in steps of 5
 MSMDxxxM10-60, xxx=440 to 450 in steps of 5
 MSMxxxAS-36, xxx =190 to 210 in steps of 5
 MSMxxxAS-18, xxx =95 to 105 in steps of 5
 SMCxxxAS-36, xxx =150 to 295 in steps of 5
 SMCxxxAS-18, xxx =5 to 145 in steps of 5
 xxx is standing for rated output power at STC.

Parameters:

Construction:	Framed, with Junction box, Cable and connectors.
Test Laboratory:	Yangzhou Opto-Electrical Products Testing Institute, No. 10 West Kaifa Road, Yangzhou 225009 Jiangsu, P. R. China.
Safety Class:	Class II
Max. system voltage:	1500V DC
Fire Safety Class:	Class C

Tested according to:

EN IEC 61730-1:2018
 EN IEC 61730-1:2018/AC:2018-06
 EN IEC 61730-2:2018
 EN IEC 61730-2:2018/AC:2018-06